

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formulation

Version 3.2 Revision Date: 09/28/2024 SDS Number: 5060440-00012 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate (with Mineral Oil) Formulation
Other means of identification : Shutout (A011866)
CEPRALOCK (89964)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Specific target organ toxicity : Category 1 (Central nervous system)
- repeated exposure

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H372 Causes damage to organs (Central nervous system)
through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**
P260 Do not breathe dust, fume, gas, mist, vapors or spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Response:
P314 Get medical attention if you feel unwell.

Disposal:
P501 Dispose of contents and container to an approved waste
disposal plant.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formulation

Version 3.2 Revision Date: 09/28/2024 SDS Number: 5060440-00012 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Bismuth hydroxide nitrate oxide	Bismuth sub-nitrate	1304-85-4	65
White mineral oil (petroleum)	Paraffinum liquidum	8042-47-5	29.4
Fatty acids, C14-26, aluminum salts	Aluminum Stearate	97404-28-9	4.8

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Get medical attention if symptoms occur.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire : Exposure to combustion products may be a hazard to health.

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

fighting

Hazardous combustion prod- : Nitrogen oxides (NOx)
ucts : Metal oxides
Carbon oxides

Specific extinguishing meth- : Use extinguishing measures that are appropriate to local cir-
ods : cumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do
so.
Evacuate area.

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
for fire-fighters : Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : Use personal protective equipment.
tive equipment and emer- : Follow safe handling advice (see section 7) and personal
gency procedures : protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages
cannot be contained.

Methods and materials for : Sweep up or vacuum up spillage and collect in suitable
containment and cleaning up : container for disposal.
Local or national regulations may apply to releases and
disposal of this material, as well as those materials and items
employed in the cleanup of releases. You will need to
determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding
certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE
CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust, fume, gas, mist, vapors or spray.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety
practice, based on the results of the workplace exposure
assessment

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formulation

Version 3.2 Revision Date: 09/28/2024 SDS Number: 5060440-00012 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

Do not eat, drink or smoke when using this product.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist - Inhalable dust)	5 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Fatty acids, C14-26, aluminum salts	97404-28-9	TWA (Respirable)	1 mg/m ³ (Aluminum)	CA BC OEL
		TWAEV (respirable dust)	5 mg/m ³	CA QC OEL
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

Engineering measures : Use feasible engineering controls to minimize exposure to compound.
All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Combined particulates and organic vapor type

Hand protection : Chemical-resistant gloves

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Eye protection : Wear safety glasses with side shields or goggles.
If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles.
Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : ointment

Color : White to light yellow

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : No data available

Evaporation rate : Not applicable

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Density	:	No data available
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics	:	
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Acute oral toxicity	:	LD50 (Rat): > 2,000 mg/kg
		Method: OECD Test Guideline 423
		Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version 3.2 Revision Date: 09/28/2024 SDS Number: 5060440-00012 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 436
Remarks: Based on data from similar materials

White mineral oil (petroleum):

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Fatty acids, C14-26, aluminum salts:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439

Result : No skin irritation

White mineral oil (petroleum):

Species : Rabbit
Result : No skin irritation

Fatty acids, C14-26, aluminum salts:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Remarks : Based on data from similar materials

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439
Remarks : Based on data from similar materials

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405

White mineral oil (petroleum):

Species : Rabbit
Result : No eye irritation

Fatty acids, C14-26, aluminum salts:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

White mineral oil (petroleum):

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula- tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Fatty acids, C14-26, aluminum salts:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative
Remarks	: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
-----------------------	---

Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative
--

Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative

White mineral oil (petroleum):

Genotoxicity in vitro	: Test Type: In vitro mammalian cell gene mutation test Result: negative
-----------------------	---

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative Remarks: Based on data from similar materials
----------------------	--

Fatty acids, C14-26, aluminum salts:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Method: OECD Test Guideline 471 Result: negative Remarks: Based on data from similar materials
-----------------------	--

Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version 3.2 Revision Date: 09/28/2024 SDS Number: 5060440-00012 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

Carcinogenicity

Not classified based on available information.

Components:

White mineral oil (petroleum):

Species : Rat
Application Route : Ingestion
Exposure time : 24 Months
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:

Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

White mineral oil (petroleum):

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: Skin contact
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Fatty acids, C14-26, aluminum salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening test

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Components:

Bismuth hydroxide nitrate oxide:

Target Organs : Central nervous system
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

White mineral oil (petroleum):

Species : Rat
LOAEL : 160 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Species : Rat
LOAEL : ≥ 1 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 4 Weeks
Method : OECD Test Guideline 412

Fatty acids, C14-26, aluminum salts:

Species : Rat
: ≥ 1000 mg/kg
Application Route : Ingestion
Exposure time : 42 Days
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Bismuth hydroxide nitrate oxide:

Ingestion : Target Organs: Blood

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Symptoms: Methaemoglobinemia
Target Organs: Central nervous system
Symptoms: Neurological disorders

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Bismuth hydroxide nitrate oxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 137 mg/l
aquatic invertebrates : Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137
plants : mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): >
137 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201

White mineral oil (petroleum):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic : NOEC (Pseudokirchneriella subcapitata (green algae)): 100
plants : mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox- : NOEC (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
icity) : Exposure time: 28 d

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 1,000 mg/l
aquatic invertebrates (Chron- : Exposure time: 21 d

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formula-tion

Version 3.2 Revision Date: 09/28/2024 SDS Number: 5060440-00012 Date of last issue: 12/06/2023
Date of first issue: 10/17/2019

ic toxicity)

Persistence and degradability

Components:

White mineral oil (petroleum):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 31 %
Exposure time: 28 d

Fatty acids, C14-26, aluminum salts:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81.2 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Fatty acids, C14-26, aluminum salts:

Partition coefficient: n- : log Pow: > 7
octanol/water Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.
Dispose of in accordance with local regulations.
Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

AICS	:	not determined
DSL	:	not determined
IECSC	:	not determined

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

SAFETY DATA SHEET

according to the Hazardous Products Regulations



Bismuth Subnitrate (with Mineral Oil) Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2023
3.2	09/28/2024	5060440-00012	Date of first issue: 10/17/2019

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/28/2024
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8