according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

SECTION 1. IDENTIFICATION

Product name : Cefquinome Liquid Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Respiratory sensitization : Category 1

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P285 In case of inadequate ventilation wear respiratory protec-

tion.

Response:

P304 + P341 IF INHALED: If breathing is difficult, remove per-

son to fresh air and keep comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a doc-

tor.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 Date of first issue: 01/06/2021 1.7 09/28/2024 7723821-00008

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Cefquinome	118443-89-3	>= 1.8595 - <= 3.125
Aluminum tristearate	637-12-7	>= 1.8595 - <= 3.125

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse. : Flush eyes with water as a precaution.

In case of eye contact

Get medical attention if irritation develops and persists.

If swallowed If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms

and effects, both acute and

delayed

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis,

reactive airways dysfunction syndrome).

Protection of first-aiders First Aid responders should pay attention to self-protection,

> and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Treat symptomatically and supportively. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- : Carbon oxides

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

ucts Nitrogen oxides (NOx)

Sulfur oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow.

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Already sensitized individuals, and those susceptible

to asthma, allergies, chronic or recurrent respiratory disease,

should consult their physician regarding working with

respiratory irritants or sensitizers.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Cefquinome	118443-89-3	TWA	2000 µg/m3 (OEB 1)	Internal
	Further information: RSEN			
Aluminum tristearate	637-12-7	TWA (Inhal- able particu- late matter)	10 mg/m³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m³	ACGIH
		TWA (Res- pirable par- ticulate mat- ter)	1 mg/m³ (Aluminum)	ACGIH

Engineering measures: Use appropriate engineering controls and manufacturing

technologies to control airborne concentrations (e.g., drip-

less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Laboratory operations do not require special containment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where

concentrations are above recommended limits or are

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection Hygiene measures : Work uniform or laboratory coat.

If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : white to off-white, off-white to beige

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

No data available

Flash point : No data available

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 0.800 - 1.100 g/cm³

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

Can react with strong oxidizing agents.

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Cefquinome:

Acute oral toxicity : LD50 (Mouse): > 5,000 mg/kg

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

Aluminum tristearate:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

Cefquinome:

Result : Irritating to skin.

Aluminum tristearate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Remarks : Based on data from similar materials

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

Components:

Cefquinome:

Result : Irritating to eyes.

Aluminum tristearate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Cefquinome:

Routes of exposure : Inhalation

Result : May cause sensitization by inhalation.

Aluminum tristearate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Aluminum tristearate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

Application Route: Ingestion

Method: OECD Test Guideline 474

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Aluminum tristearate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Fertility/early embryonic development

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:

Cefquinome:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Aluminum tristearate:

Species : Rat

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

NOAEL : >= 5,000 mg/kg Application Route : Ingestion

Exposure time : 90 Days

Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Cefquinome:

Inhalation : Symptoms: anaphylaxis, bronchospasm, Cough, respiratory

tract irritation, Rash, rhinitis, runny nose, sneezing

Remarks: May produce an allergic reaction.

Skin contact : Remarks: May irritate skin.

May produce an allergic reaction.

Eye contact : Remarks: May irritate eyes.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Cefquinome:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 500 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 86 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 37

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

EC50 (Anabaena flos-aquae (cyanobacterium)): 0.041 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Anabaena flos-aquae (cyanobacterium)): 0.014 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version 1.7

Revision Date: 09/28/2024

SDS Number: 7723821-00008 Date of last issue: 09/30/2023 Date of first issue: 01/06/2021

Test Type: Respiration inhibition Method: OECD Test Guideline 209

NOEC: 295.3 mg/l Exposure time: 3 h

Test Type: Respiration inhibition Method: OECD Test Guideline 209

Aluminum tristearate:

Ecotoxicology Assessment

Acute aquatic toxicity Toxic effects cannot be excluded

Chronic aquatic toxicity Toxic effects cannot be excluded

Persistence and degradability

Components:

Cefquinome:

Biodegradability Result: not rapidly degradable

> Biodegradation: 40 % Exposure time: 30 d

Method: OECD Test Guideline 302B

Stability in water Hydrolysis: > 90 % (5 d)

Method: FDA 3.09

Bioaccumulative potential

Components:

Cefquinome:

Partition coefficient: n-

octanol/water

log Pow: -2.01

Mobility in soil

Components:

Cefquinome:

Distribution among environ- : log Koc: 2.76 mental compartments

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging Empty containers should be taken to an approved waste

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Cefquinome)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Cefquinome)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo : 964

aircraft)

Packing instruction (passen: 964

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S.

(Cefquinome)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.

(Cefquinome)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171

Marine pollutant : yes(Cefquinome)

Remarks : Above applies only to containers over 119 gallons or 450

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

liters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Glycerides, mixed decanoyl and octanoyl 73398-61-5
Aluminum tristearate 637-12-7
Cefquinome 118443-89-3

California Permissible Exposure Limits for Chemical Contaminants

Aluminum tristearate 637-12-7

The ingredients of this product are reported in the following inventories:

DSL : not determined

AICS : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System: IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance

according to the OSHA Hazard Communication Standard



Cefquinome Liquid Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 1.7 09/28/2024 7723821-00008 Date of first issue: 01/06/2021

Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to

compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/28/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8