according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

SECTION 1. IDENTIFICATION

Product name : Cephalonium Formulation Other means of identification : Cepravin Dry Cow (A003322)

COOPERS CEPRAVIN DRY COW INTRAMAMMARY

ANTIBIOTIC (47940)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Respiratory sensitization : Category 1

Skin sensitization : Category 1

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing diffi-

culties if inhaled.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing should not be allowed out of

the workplace.

P280 Wear protective gloves. P284 Wear respiratory protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

CENTER.

P302 + P352 IF ON SKIN: Wash with plenty of water. P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing. P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P342 + P311 If experiencing respiratory symptoms: Call a doc-

tor.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Paraffin oil	No data availa- ble	8012-95-1	>= 80 - <= 100 *
Cefalonium	Pyridinium, 4- carbamoyl-1- ((2-carboxy-8- oxo-7-(2-(2- thienyl)acetamid o)-5-thia-1-aza- bicyclo(4. 2.0)oct-2-en-3- yl)methyl)- hy- droxide,	5575-21-3	>= 5 - < 10 *
Hydroxyaluminum dis- tearate	Aluminum, hydroxybis(octade canoato-l.kappa.O)-	300-92-5	>= 1 - < 5 *

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

according to the Hazardous Products Regulations



Cephalonium Formulation

Version **Revision Date:** SDS Number: Date of last issue: 07/06/2024 09/28/2024 26950-00028 Date of first issue: 10/31/2014 7.1

If inhaled If inhaled, remove to fresh air.

> If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting. If swallowed

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

delayed

May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis,

reactive airways dysfunction syndrome).

Protection of first-aiders First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Nitrogen oxides (NOx)

Sulfur oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment: In the event of fire, wear self-contained breathing apparatus.

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 09/28/2024 26950-00028 Date of first issue: 10/31/2014 7.1

for fire-fighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation

Advice on safe handling

Use only with adequate ventilation.

Do not get on skin or clothing. Do not breathe mist or vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Keep container tightly closed.

Already sensitized individuals, and those susceptible

to asthma, allergies, chronic or recurrent respiratory disease,

should consult their physician regarding working with

respiratory irritants or sensitizers.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage Keep in properly labeled containers.

Store locked up.

according to the Hazardous Products Regulations



Cephalonium Formulation

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/06/2024

 7.1
 09/28/2024
 26950-00028
 Date of first issue: 10/31/2014

Keep tightly closed.

Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
Dane (Caral)	0040.05.4	exposure)	concentration	04 40 051
Paraffin oil	8012-95-1	TWA (Mist)	5 mg/m³	CA AB OEL
		STEL (Mist)	10 mg/m³	CA AB OEL
		TWAEV (Mist	5 mg/m³	CA QC OEL
		- Inhalable		
		dust)		
		TWA (Mist)	1 mg/m³	CA BC OEL
		TWA	5 mg/m³	ACGIH
		(Inhalable		
		particulate		
		matter)		
Cefalonium	5575-21-3	TWA	2000 μg/m3 (OEB 1)	Internal
	Further information: RSEN		'/	
Hydroxyaluminum distearate	300-92-5	TWA	10 mg/m³	CA AB OEL
Trydroxyaldmindm distearate	300-32-3	TWA (Res-	1 mg/m ³	CA BC OEL
		pirable)	(Aluminum)	CA BC OEL
		TWAEV	10 mg/m ³	CA QC OEL
			ŭ	CA GC OEL
		TWA (Inhal- able)	10 mg/m³	CA BC OEL
		TWA (Res-	3 mg/m³	CA BC OEL
		pirable)	J 3	
		TWAEV	5 mg/m³	CA QC OEL
		(respirable	J 3	
		dust)		
		TWA	10 mg/m³	ACGIH
		(Inhalable	, g ,	
		particulate		
		matter)		
		TWA	3 mg/m³	ACGIH
		(Respirable	Jg,	
		particulate		
		matter)		
		TWA	1 mg/m³	ACGIH
		(Respirable	(Aluminum)	,
		particulate	(*)	
		matter)		
	1	matter	1	

Engineering measures : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations.

Personal protective equipment

according to the Hazardous Products Regulations



Cephalonium Formulation

Version **Revision Date:** SDS Number: Date of last issue: 07/06/2024 09/28/2024 26950-00028 Date of first issue: 10/31/2014 7.1

If adequate local exhaust ventilation is not available or Respiratory protection

exposure assessment demonstrates exposures outside the

recommended guidelines, use respiratory protection.

Combined particulates and organic vapor type

Filter type

Hand protection

Material

Chemical-resistant gloves

Remarks Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection Wear the following personal protective equipment:

Safety glasses

Skin and body protection Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

If exposure to chemical is likely during typical use, provide Hygiene measures

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance suspension

Color off-white

Odor odorless

Odor Threshold No data available

No data available pΗ

Melting point/freezing point No data available

Initial boiling point and boiling

range

No data available

Flash point No data available

Evaporation rate No data available

Flammability (solid, gas) No data available

Flammability (liquids) No data available

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : None known. Incompatible materials : None.

Hazardous decomposition

products

No hazardous decomposition products are known.

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Paraffin oil:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Cefalonium:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Hydroxyaluminum distearate:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg

Method: OECD Test Guideline 423

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Skin corrosion/irritation

Not classified based on available information.

Components:

Paraffin oil:

Species : Rabbit

Result : No skin irritation

Hydroxyaluminum distearate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Remarks : Based on data from similar materials

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 439

Remarks : Based on data from similar materials

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Paraffin oil:

Species : Rabbit

Result : No eye irritation

Hydroxyaluminum distearate:

Species : Bovine cornea

Method : OECD Test Guideline 437

Remarks : Based on data from similar materials

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Cefalonium:

Routes of exposure : Skin contact

Assessment : Probability or evidence of skin sensitization in humans

Routes of exposure : Inhalation

Assessment : May cause sensitization by inhalation.

Hydroxyaluminum distearate:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Cefalonium:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: Ingestion

Result: negative

Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Rat

Application Route: Ingestion

Result: negative

Hydroxyaluminum distearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Cefalonium:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Hydroxyaluminum distearate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Two-generation reproduction toxicity study

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Paraffin oil:

Species : Rat, female LOAEL : 161 mg/kg Application Route : Ingestion Exposure time : 90 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Paraffin oil:

Toxicity to fish : LL50 (Scophthalmus maximus (turbot)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Acartia tonsa (Calanoid copepod)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EL50 (Skeletonema costatum (marine diatom)): > 100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

NOELR (Skeletonema costatum (marine diatom)): > 1 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction Remarks: Based on data from similar materials

Cefalonium:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic

plants

NOEC (Anabaena flos-aquae (cyanobacterium)): 0.213 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

ErC50 (Anabaena flos-aquae (cyanobacterium)): 0.315 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

NOEC: 0.48 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Hydroxyaluminum distearate:

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Cefalonium:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 32 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Hydroxyaluminum distearate:

Biodegradability : Result: Readily biodegradable.

Remarks: Based on data from similar materials

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

Bioaccumulative potential

Components:

Paraffin oil:

Partition coefficient: n- : log Pow: > 4

octanol/water Remarks: Calculation

Cefalonium:

Partition coefficient: n- : log Pow: 0.188

octanol/water

Hydroxyaluminum distearate:

Partition coefficient: n- : log Pow: 15.088 octanol/water : Remarks: Calculation

Mobility in soil
No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

Not regulated as a dangerous good

Special precautions for user

Not applicable

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA AB OEL / STEL : 15-minute occupational exposure limit

CA BC OEL / TWA : 8-hour time weighted average

CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Tempera-

according to the Hazardous Products Regulations



Cephalonium Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 7.1 09/28/2024 26950-00028 Date of first issue: 10/31/2014

ture; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to

compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/28/2024 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8