

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version 9.1 Revision Date: 09/28/2024 SDS Number: 26978-00027 Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

SECTION 1. IDENTIFICATION

Product name : Cephalonium Formulation
Other means of identification : Cpraviv Dry Cow (A003322)
COOPERS CEPRAVIN DRY COW INTRAMAMMARY
ANTIBIOTIC (47940)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use


Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Respiratory sensitization : Category 1
Skin sensitization : Category 1
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary Statements : **Prevention:**
P261 Avoid breathing mist or vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
P285 In case of inadequate ventilation wear respiratory protection.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version 9.1 Revision Date: 09/28/2024 SDS Number: 26978-00027 Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P341 IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P342 + P311 If experiencing respiratory symptoms: Call a doctor.
P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Paraffin oil	8012-95-1	$\geq 90 - \leq 100$
Cefalonium	5575-21-3	$\geq 5 - < 10$
Hydroxyaluminum distearate	300-92-5	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If breathing is difficult, give oxygen.
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

-
- | | | |
|---|---|---|
| If swallowed | : | If swallowed, DO NOT induce vomiting.
If vomiting occurs have person lean forward.
Call a physician or poison control center immediately.
Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, both acute and delayed | : | May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome). |
| Protection of first-aiders | : | First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8). |
| Notes to physician | : | Treat symptomatically and supportively. |
-

SECTION 5. FIRE-FIGHTING MEASURES

- | | | |
|--|---|---|
| Suitable extinguishing media | : | Water spray
Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards during fire fighting | : | Exposure to combustion products may be a hazard to health. |
| Hazardous combustion products | : | Carbon oxides
Nitrogen oxides (NO _x)
Sulfur oxides
Metal oxides |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area. |
| Special protective equipment for fire-fighters | : | In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment. |
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8). |
| Environmental precautions | : | Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version 9.1 Revision Date: 09/28/2024 SDS Number: 26978-00027 Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.
Do not breathe mist or vapors.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Already sensitized individuals, and those susceptible to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respiratory irritants or sensitizers.
Take care to prevent spills, waste and minimize release to the environment.

Conditions for safe storage : Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations.

Materials to avoid : No special restrictions on storage with other products.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version 9.1 Revision Date: 09/28/2024 SDS Number: 26978-00027 Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

Paraffin oil	8012-95-1	TWA (Mist)	5 mg/m ³	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
		TWA (Mist)	5 mg/m ³	NIOSH REL
		ST (Mist)	10 mg/m ³	NIOSH REL
Cefalonium	5575-21-3	TWA	2000 µg/m ³ (OEB 1)	Internal
Further information: RSEN				
Hydroxyaluminum distearate	300-92-5	TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	1 mg/m ³ (Aluminum)	ACGIH

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment: Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Hygiene measures : Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).
: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Contaminated work clothing should not be allowed out of the workplace.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	suspension
Color	:	off-white
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	No data available
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle characteristics		
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	None known.
Incompatible materials	:	None.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

Paraffin oil:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit): > 2,000 mg/kg Assessment: The substance or mixture has no acute dermal toxicity

Cefalonium:

Acute oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
---------------------	---	---------------------------

Hydroxylaluminum distearate:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.15 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Skin corrosion/irritation

Not classified based on available information.

Components:

Paraffin oil:

Species : Rabbit
Result : No skin irritation

Hydroxyaluminum distearate:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 431
Remarks : Based on data from similar materials

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439
Remarks : Based on data from similar materials

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Paraffin oil:

Species : Rabbit
Result : No eye irritation

Hydroxyaluminum distearate:

Species : Bovine cornea
Method : OECD Test Guideline 437
Remarks : Based on data from similar materials

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version 9.1 Revision Date: 09/28/2024 SDS Number: 26978-00027 Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

Cefalonium:

Routes of exposure : Skin contact
Assessment : Probability or evidence of skin sensitization in humans

Routes of exposure : Inhalation
Assessment : May cause sensitization by inhalation.

Hydroxyaluminum distearate:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Method : OECD Test Guideline 429
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Cefalonium:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Test Type: Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Rat
Application Route: Ingestion
Result: negative

Test Type: Unscheduled DNA synthesis (UDS) test with mammalian liver cells in vivo
Species: Rat
Application Route: Ingestion
Result: negative

Hydroxyaluminum distearate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Cefalonium:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative

Hydroxyaluminum distearate:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version 9.1 Revision Date: 09/28/2024 SDS Number: 26978-00027 Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

Repeated dose toxicity

Components:

Paraffin oil:

Species : Rat, female
LOAEL : 161 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:

Paraffin oil:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Paraffin oil:

Toxicity to fish : LL50 (Scophthalmus maximus (turbot)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Acartia tonsa (Calanoid copepod)): > 100 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Skeletonema costatum (marine diatom)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

NOELR (Skeletonema costatum (marine diatom)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Cefalonium:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic plants : NOEC (Anabaena flos-aquae (cyanobacterium)): 0.213 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

ErC50 (Anabaena flos-aquae (cyanobacterium)): 0.315 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

NOEC: 0.48 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Hydroxyaluminum distearate:

Ecotoxicology Assessment

Chronic aquatic toxicity : No toxicity at the limit of solubility.

Persistence and degradability

Components:

Cefalonium:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 32 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Hydroxyaluminum distearate:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Paraffin oil:

Partition coefficient: n-octanol/water : log Pow: > 4
Remarks: Calculation

Cefalonium:

Partition coefficient: n-octanol/water : log Pow: 0.188

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Hydroxyaluminum distearate:

Partition coefficient: n-octanol/water : log Pow: 15.088
Remarks: Calculation

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

SARA 311/312 Hazards : Respiratory or skin sensitization
Aspiration hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Paraffin oil	8012-95-1
Cefalonium	5575-21-3

California List of Hazardous Substances

Paraffin oil	8012-95-1
--------------	-----------

California Permissible Exposure Limits for Chemical Contaminants

Paraffin oil	8012-95-1
Hydroxyaluminum distearate	300-92-5

The ingredients of this product are reported in the following inventories:

AICS	: not determined
DSL	: not determined
IECSC	: not determined

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation


Version
9.1

Revision Date:
09/28/2024

SDS Number:
26978-00027

Date of last issue: 07/06/2024
Date of first issue: 10/31/2014

NFPA 704:



HMIS® IV:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Cephalonium Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 07/06/2024
9.1	09/28/2024	26978-00027	Date of first issue: 10/31/2014

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/28/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8