according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

SECTION 1. IDENTIFICATION

Product name : Copper Oxide Solid Formulation

Other means of identification : COOPERS PERMATRACE COPPER 10 CAPSULES FOR

CALVES AND ADULT CATTLE (47689)

COOPERS PERMATRACE COPPER 20 CAPSULES FOR

CATTLE (47688)

COOPERS PERMATRACE COPPER CAPSULES FOR

ADULT SHEEP & GOATS (47637)

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P280 Wear protective gloves, protective clothing, eye protection

and face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version **Revision Date:** SDS Number: Date of last issue: 07/06/2024 09/28/2024 11153935-00008 Date of first issue: 12/20/2022 4.1

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

Dust contact with the eyes can lead to mechanical irritation.

Contact with dust can cause mechanical irritation or drying of the skin.

May form explosive dust-air mixture during processing, handling or other means.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Calcium carbonate		471-34-1	4.9
Diiron trioxide	No data availa- ble	1309-37-1	1
tert-Butyl-4- methoxyphenol	Phenol, (1,1-dimethylethyl)-4-methoxy-	25013-16-5	0.4

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention.

In case of contact, immediately flush skin with soap and plenty In case of skin contact

of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

Most important symptoms

Suspected of causing cancer.

and effects, both acute and

Suspected of damaging the unborn child.

delayed

Contact with dust can cause mechanical irritation or drying of

Dust contact with the eyes can lead to mechanical irritation.

Protection of first-aiders First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

when the potential for exposure exists (see section 8).

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod: :

ucts

Carbon oxides

Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not breathe dust.

Do not swallow.

Avoid contact with eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Calcium carbonate	471-34-1	TWAEV (to- tal dust)	10 mg/m³	CA QC OEL
		TWA	10 mg/m³ (Calcium car- bonate)	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m³	CA BC OEL
		STEL	20 mg/m ³	CA BC OEL
Diiron trioxide	1309-37-1	TWA (Respirable)	5 mg/m ³	CA AB OEL
		TWA (Fumes)	5 mg/m³ (Iron)	CA BC OEL
		TWA (Dust)	5 mg/m³ (Iron)	CA BC OEL
		STEL	10 mg/m ³	CA BC OEL

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

(Fumes)	(Iron)	
TWAEV (fume and dust)	5 mg/m³ (Iron)	CA QC OEL
TWA (Respirable particulate matter)	5 mg/m³	ACGIH

Engineering measures : Use feasible engineering controls to minimize exposure to

compound.

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or

exposure assessment demonstrates exposures outside the

recommended guidelines, use respiratory protection.

Filter type

Hand protection

Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.

Particulates type

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection

Hygiene measures

Work uniform or laboratory coat.

If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the

use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : capsule

Color : metallic

gray

Odor : No data available

Odor Threshold : No data available

pH : No data available

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture during processing,

handling or other means.

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

Reactivity : Not classified as a reactivity hazard. Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture during processing,

handling or other means.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation. Oxidizing agents

Incompatible materials
Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Calcium carbonate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 420

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 3 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Diiron trioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): > 5.05 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

tert-Butyl-4-methoxyphenol:

Acute oral toxicity : LD50 (Rabbit): 2,100 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Calcium carbonate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Diiron trioxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

tert-Butyl-4-methoxyphenol:

Species : Rabbit Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Calcium carbonate:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Diiron trioxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

tert-Butyl-4-methoxyphenol:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days Remarks : Based on data from similar materials

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 09/28/2024 11153935-00008 Date of first issue: 12/20/2022 4.1

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Calcium carbonate:

Test Type Local lymph node assay (LLNA)

Routes of exposure Skin contact

Species Mouse

Method **OECD Test Guideline 429**

Result negative

tert-Butyl-4-methoxyphenol:

Human repeat insult patch test (HRIPT) Test Type

Routes of exposure Skin contact Result negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Calcium carbonate:

Genotoxicity in vitro Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Diiron trioxide:

Genotoxicity in vitro Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo Test Type: In vivo mammalian alkaline comet assay

Species: Rat

Application Route: Ingestion

Method: OECD Test Guideline 489

Result: negative

tert-Butyl-4-methoxyphenol:

Genotoxicity in vitro Test Type: Bacterial reverse mutation assay (AMES)

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: negative

Carcinogenicity

Suspected of causing cancer.

Components:

tert-Butyl-4-methoxyphenol:

Species: RatApplication Route: IngestionExposure time: 104 weeksResult: positive

Species : Hamster, male
Application Route : Ingestion
Exposure time : 24 weeks
Result : positive

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Suspected of damaging the unborn child.

Components:

Calcium carbonate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

tert-Butyl-4-methoxyphenol:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Fertility/early embryonic development

Species: Mouse

Application Route: Ingestion

Result: positive

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on development, based on

animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Calcium carbonate:

Species : Rat

NOAEL : > 1,000 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

Method : OECD Test Guideline 422

Diiron trioxide:

Species : Rat

NOAEL : >= 1,000 mg/kg

Application Route : Ingestion Exposure time : 90 Days

Method : OECD Test Guideline 408

tert-Butyl-4-methoxyphenol:

Species : Rat
NOAEL : 50 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion
Exposure time : 8 Months

Aspiration toxicity

Not classified based on available information.

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Calcium carbonate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): 50

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

EL50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC: 1,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

EC50: > 1,000 mg/l Exposure time: 3 h

Method: OECD Test Guideline 209

Diiron trioxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 10,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Raphidocelis subcapitata (freshwater green alga)): > 20

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOELR (Raphidocelis subcapitata (freshwater green alga)):

>= 20 mg/l

Exposure time: 72 h

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version **Revision Date:** SDS Number: Date of last issue: 07/06/2024 09/28/2024 11153935-00008 Date of first issue: 12/20/2022 4.1

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): >= 20 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to microorganisms EL50 (activated sludge): >= 100 mg/l

Exposure time: 3 h Method: ISO 8192

Remarks: Based on data from similar materials

tert-Butyl-4-methoxyphenol:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 1.56 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 2.3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 1.9

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.25

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

No data available

Bioaccumulative potential

Components:

tert-Butyl-4-methoxyphenol:

Bioaccumulation Species: Oryzias latipes (Orange-red killifish)

Bioconcentration factor (BCF): 16 - 21

Partition coefficient: n-

octanol/water

log Pow: 2.82

Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of waste into sewer.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo :

aircraft)

Packing instruction (passen- : 956

ger aircraft)

Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

956

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

TDG

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

N.O.S.

(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Class : 9
Packing group : III
Labels : 9
ERG Code : 171

Marine pollutant : yes(Copper oxide, 2,6-Di-tert-butyl-p-cresol)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CA AB OEL : Canada. Alberta, Occupational Health and Safety Code (table

2: OEL)

CA BC OEL : Canada. British Columbia OEL

CA QC OEL : Québec. Regulation respecting occupational health and safe-

ty, Schedule 1, Part 1: Permissible exposure values for air-

borne contaminants

ACGIH / TWA : 8-hour, time-weighted average
CA AB OEL / TWA : 8-hour Occupational exposure limit
CA BC OEL / TWA : 8-hour time weighted average
CA BC OEL / STEL : short-term exposure limit

CA QC OEL / TWAEV : Time-weighted average exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International

according to the Hazardous Products Regulations



Copper Oxide Solid Formulation

Version Revision Date: SDS Number: Date of last issue: 07/06/2024 4.1 09/28/2024 11153935-00008 Date of first issue: 12/20/2022

Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/28/2024 Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8