according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

#### **SECTION 1. IDENTIFICATION**

Product name : Deltamethrin (with Xylene) Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product Restrictions on use : Not applicable

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1B

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3

Specific target organ toxicity

- repeated exposure (Oral)

Category 1 (Central nervous system, Immune system)

Specific target organ toxicity

- repeated exposure

(Inhalation)

Category 1 (Central nervous system)

Specific target organ toxicity

- repeated exposure

Category 2 (Auditory system)

Aspiration hazard : Category 1

according to the OSHA Hazard Communication Standard



## Deltamethrin (with Xylene) Formulation

Version 6.3

Revision Date: 09/28/2024

SDS Number: 2972467-00018

Date of last issue: 06/26/2024 Date of first issue: 07/02/2018

#### **GHS** label elements

Hazard pictograms







Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H302 + H332 Harmful if swallowed or if inhaled. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H340 May cause genetic defects.

H350 May cause cancer.

H361fd Suspected of damaging fertility. Suspected of damaging

the unborn child.

H372 Causes damage to organs (Central nervous system, Immune system) through prolonged or repeated exposure if swal-

lowed.

H372 Causes damage to organs (Central nervous system)

through prolonged or repeated exposure if inhaled.

H373 May cause damage to organs (Auditory system) through

prolonged or repeated exposure.

### **Precautionary Statements**

#### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat, sparks, open flame and hot surfaces. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves, protective clothing, eye protection and face protection.

### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

all contaminated clothing. Rinse skin with water.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical attention.

P331 Do NOT induce vomiting.

P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P337 + P313 If eye irritation persists: Get medical attention. P362 + P364 Take off contaminated clothing and wash it before reuse.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### Other hazards

Cutaneous sensations may occur, such as burning or stinging on the face and mucosae. However, these sensations cause no lesions and are of a transitory nature (max. 24 hours). Vapors may form explosive mixture with air.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Ethylbenzene	100-41-4	>= 30 - < 50
Xylene	1330-20-7	>= 30 - < 50
Deltamethrin (ISO)	52918-63-5	>= 5 - < 10
2,6-Di-tert-butyl-p-cresol	128-37-0	>= 1 - < 5
Solvent naphtha (petroleum), light	64742-95-6	>= 0.1 - < 1
aromatic		
Methanol	67-56-1	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

### **SECTION 4. FIRST AID MEASURES**

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Get medical attention.

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

In case of skin contact : In case of contact, immediately flush skin with plenty of water

for at least 15 minutes while removing contaminated clothing

and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed : If swallowed, DO NOT induce vomiting.

If vomiting occurs have person lean forward.

Call a physician or poison control center immediately.

Rinse mouth thoroughly with water.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and

delayed

Harmful if swallowed or if inhaled.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause genetic defects.

May cause cancer.

Suspected of damaging fertility. Suspected of damaging the

unborn child.

Causes damage to organs through prolonged or repeated

exposure if swallowed.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

This product contains a pyrethroid.

Pyrethroid poisoning should not be confused with carbamate

or organophosphate poisoning.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

: Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

according to the OSHA Hazard Communication Standard



## Deltamethrin (with Xylene) Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Hazardous combustion prod- :

ucts

Carbon oxides

Nitrogen oxides (NOx) Bromine compounds

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment:

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Remove all sources of ignition.

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

**Environmental precautions** 

Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material

can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust

ventilation.

Use explosion-proof electrical, ventilating and lighting equip-

ment

Advice on safe handling : Do not get on skin or clothing.

Do not breathe mist or vapors.

Do not swallow. Do not get in eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Non-sparking tools should be used. Keep container tightly closed.

Already sensitized individuals, and those susceptible

to asthma, allergies, chronic or recurrent respiratory disease,

should consult their physician regarding working with

respiratory irritants or sensitizers.

Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store locked up. Keep tightly closed.

Keep in a cool, well-ventilated place.

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

Self-reactive substances and mixtures

Organic peroxides Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases Explosives Gases

Very acutely toxic substances and mixtures

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethylbenzene	100-41-4	TWA	20 ppm	ACGIH
		TWA	100 ppm	NIOSH REL

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

	Ī		•	•
			435 mg/m <sup>3</sup>	
		ST	125 ppm	NIOSH REL
			545 mg/m <sup>3</sup>	
		TWA	100 ppm	OSHA Z-1
			435 mg/m <sup>3</sup>	
Xylene	1330-20-7	TWA	100 ppm	OSHA Z-1
			435 mg/m <sup>3</sup>	
		TWA	20 ppm	ACGIH
Deltamethrin (ISO)	52918-63-5	TWA	15 μg/m3 (OEB 3)	Internal
	Further inform	nation: DSEN, Sk	in	
		Wipe limit	100 μg/100 cm <sup>2</sup>	Internal
2,6-Di-tert-butyl-p-cresol	128-37-0	TWA (Inhal-	2 mg/m³	ACGIH
		able fraction		
		and vapor)		
		TWA	10 mg/m <sup>3</sup>	NIOSH REL
Solvent naphtha (petroleum),	64742-95-6	TWA	500 ppm	OSHA Z-1
light aromatic			2,000 mg/m <sup>3</sup>	
		TWA	200 mg/m <sup>3</sup>	ACGIH
			(total hydrocarbon	
			vapor)	
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		ST	250 ppm	NIOSH REL
			325 mg/m <sup>3</sup>	
		TWA	200 ppm	NIOSH REL
			260 mg/m <sup>3</sup>	
		TWA	200 ppm	OSHA Z-1
			260 mg/m <sup>3</sup>	

## **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift (As soon as possible after exposure ceases)	150 mg/g creatinine	ACGIH BEI
Xylene	1330-20-7	Methylhippu ric acids	Urine	End of shift (As soon as possible after exposure ceases)	0.3 g/g creatinine	ACGIH BEI
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after	15 mg/l	ACGIH BEI

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/26/2024

 6.3
 09/28/2024
 2972467-00018
 Date of first issue: 07/02/2018

exposure ceases)

**Engineering measures** : Use appropriate engineering controls and manufacturing

technologies to control airborne concentrations (e.g., drip-

less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

protect products, workers, and the environment.

Containment technologies suitable for controlling compounds are required to control at source and to prevent migration of

the compound to uncontrolled areas (e.g., open-face

containment devices). Minimize open handling.

Use explosion-proof electrical, ventilating and lighting

equipment.

#### Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are

unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving. Take note that the product is

flammable, which may impact the selection of hand

protection.

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection : Work uniform or laboratory coat.

Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.

Use appropriate degowning techniques to remove potentially

contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: 6.3 09/28/2024

SDS Number: 2972467-00018

Date of last issue: 06/26/2024 Date of first issue: 07/02/2018

workplace.

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : clear

yellow

Odor : No data available

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point :  $100 \,^{\circ}\text{F} / 38 \,^{\circ}\text{C}$ 

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Not applicable

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : No data available

Solubility(ies)

Water solubility : No data available

Partition coefficient: n- : Not applicable

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

octanol/water

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics

Particle size : Not applicable

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Flammable liquid and vapor.

tions

tions

Vapors may form explosive mixture with air. Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition : N

products

No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

#### **Acute toxicity**

Harmful if swallowed or if inhaled.

**Product:** 

Acute oral toxicity : Acute toxicity estimate: 997.09 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Components:

Ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.8 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Xylene:

Acute oral toxicity : LD50 (Rat): 3,523 mg/kg

Method: Directive 67/548/EEC, Annex V, B.1.

Acute inhalation toxicity : LC50 (Rat): 27.571 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 4,200 mg/kg

Deltamethrin (ISO):

Acute oral toxicity : LD50 (Rat): 66.7 mg/kg

LD50 (Rat): 9 - 139 mg/kg

LD50 (Mouse): 19 - 34 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.8 mg/l

Exposure time: 2 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 2,000 mg/kg

LD50 (Rat): > 800 mg/kg

Acute toxicity (other routes of :

administration)

LD50 (Rat): 2.5 mg/kg

Application Route: Intravenous

LD50 (Mouse): 10 mg/kg

Application Route: Intraperitoneal

2,6-Di-tert-butyl-p-cresol:

Acute oral toxicity : LD50 (Rat): > 6,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Solvent naphtha (petroleum), light aromatic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.61 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg

Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Remarks: Based on national or regional regulation.

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg

Method: Expert judgment

Remarks: Based on national or regional regulation.

Skin corrosion/irritation

Causes skin irritation.

**Components:** 

Xylene:

Species : Rabbit
Result : Skin irritation

Deltamethrin (ISO):

Species : Rabbit

Result : No skin irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Remarks : Based on data from similar materials

Solvent naphtha (petroleum), light aromatic:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Methanol:

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Species : Rabbit

Result : No skin irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### **Components:**

Xylene:

Species : Rabbit

Result : Irritation to eyes, reversing within 21 days

Deltamethrin (ISO):

Species : Rabbit

Result : Moderate eye irritation

2,6-Di-tert-butyl-p-cresol:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Remarks : Based on data from similar materials

Solvent naphtha (petroleum), light aromatic:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Methanol:

Species : Rabbit

Result : No eye irritation

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

### **Components:**

Xylene:

Test Type : Local lymph node assay (LLNA)

Routes of exposure : Skin contact Species : Mouse Result : negative

Deltamethrin (ISO):

Test Type : Maximization Test

Routes of exposure : Dermal

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Species : Guinea pig Result : negative

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Dermal Species : Humans Result : positive

2,6-Di-tert-butyl-p-cresol:

Test Type : Human repeat insult patch test (HRIPT)

Routes of exposure : Skin contact Species : Humans Result : negative

Solvent naphtha (petroleum), light aromatic:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Methanol:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

Germ cell mutagenicity

May cause genetic defects.

**Components:** 

**Ethylbenzene:** 

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Unscheduled DNA synthesis (UDS) test with

mammalian liver cells in vivo

Species: Mouse

Application Route: Inhalation Method: OECD Test Guideline 486

Result: negative

Xylene:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: 6.3 09/28/2024

SDS Number: 2972467-00018

Date of last issue: 06/26/2024 Date of first issue: 07/02/2018

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: In vitro sister chromatid exchange assay in mam-

malian cells Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Skin contact

Result: negative

Deltamethrin (ISO):

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: DNA Repair Test system: Escherichia coli

Result: negative

Test Type: Chromosomal aberration
Test system: Chinese hamster ovary cells

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells Concentration: LOAEL: 20 mg/kg

Result: positive

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse Application Route: Oral Result: negative

Test Type: dominant lethal test

Species: Mouse Application Route: Oral Result: negative

Test Type: sister chromatid exchange assay

Species: Mouse Cell type: Bone marrow Application Route: Oral Result: negative

2,6-Di-tert-butyl-p-cresol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow

cytogenetic test, chromosomal analysis)

Species: Rat

**Application Route: Ingestion** 

Result: negative

Solvent naphtha (petroleum), light aromatic:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: positive

Genotoxicity in vivo : Test Type: Sister chromatid exchange analysis in spermato-

gonia

Species: Mouse

Application Route: Intraperitoneal injection

Result: positive

Germ cell mutagenicity -

Assessment

: Positive result(s) from in vivo heritable germ cell mutagenicity

tests in mammals

Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: in vitro micronucleus test

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Carcinogenicity

May cause cancer.

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

#### Components:

Ethylbenzene:

Species : Rat

Application Route : inhalation (vapor)
Exposure time : 104 weeks
Result : positive

Remarks : The mechanism or mode of action may not be relevant in hu-

mans.

Xylene:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative

Deltamethrin (ISO):

Species : Mouse, male and female

Application Route : oral (feed) Exposure time : 104 weeks

NOAEL : 8 mg/kg body weight LOAEL : 4 mg/kg body weight

Result : positive Target Organs : Lymph nodes

Species : Rat, male and female

Application Route : oral (feed)
Exposure time : 2 Years
Result : negative

Species : Dog, male and female

Application Route : oral (feed) Exposure time : 2 Years

NOAEL : 1 mg/kg body weight

Result : negative

2,6-Di-tert-butyl-p-cresol:

Species: RatApplication Route: IngestionExposure time: 22 MonthsResult: negative

Solvent naphtha (petroleum), light aromatic:

Species : Mouse
Application Route : Skin contact
Exposure time : 2 Years
Result : positive

Carcinogenicity - Assess-

ment

: Sufficient evidence of carcinogenicity in animal experiments

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Methanol:

Species : Monkey

Application Route : inhalation (vapor)

Exposure time : 7 Months
Result : negative

IARC Group 2B: Possibly carcinogenic to humans

Ethylbenzene 100-41-4

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Suspected of damaging fertility. Suspected of damaging the unborn child.

**Components:** 

Ethylbenzene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor) Method: OECD Test Guideline 416

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Inhalation Method: OECD Test Guideline 414

Result: negative

Xylene:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Deltamethrin (ISO):

Effects on fertility : Test Type: Three-generation reproduction toxicity study

Species: Rat

Application Route: oral (feed)

Early Embryonic Development: NOAEL: 50 mg/kg body

veight

Symptoms: No effects on fertility., Embryo-fetal toxicity. Remarks: Significant toxicity observed in testing

according to the OSHA Hazard Communication Standard



## Deltamethrin (with Xylene) Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Test Type: Two-generation reproduction toxicity study

Species: Rat

**Application Route: Oral** 

Early Embryonic Development: LOAEL: 84 - 149 mg/kg body

weight

Symptoms: No effects on fertility., Embryo-fetal toxicity.

Test Type: Fertility Species: Rat, male Application Route: Oral

Fertility: LOAEL: 1 mg/kg body weight

Symptoms: Effects on fertility.

**Target Organs: Testes** 

Effects on fetal development : Test Type: Development

Species: Mouse

Application Route: oral (gavage)

Developmental Toxicity: LOAEL: 1 mg/kg body weight

Result: Skeletal malformations. Remarks: Maternal toxicity observed.

Test Type: Development Species: Rat, female

Developmental Toxicity: NOAEL: 10 mg/kg body weight

Symptoms: No effects on fetal development.

Test Type: Development Species: Rabbit, female

Application Route: oral (gavage)

Developmental Toxicity: NOAEL: 16 mg/kg body weight

Symptoms: No effects on fetal development.

Reproductive toxicity - As-

sessment

Some evidence of adverse effects on sexual function and

fertility, and/or on development, based on animal experiments.

2,6-Di-tert-butyl-p-cresol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

**Application Route: Ingestion** 

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Solvent naphtha (petroleum), light aromatic:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening

test

Species: Rat

Application Route: inhalation (vapor)

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: inhalation (vapor)

Result: negative

Methanol:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Monkey

Application Route: inhalation (vapor)

Result: negative

Effects on fetal development : Test Type: Reproduction/Developmental toxicity screening

test

Species: Monkey

Application Route: inhalation (vapor)

Result: negative

STOT-single exposure

May cause respiratory irritation.

**Components:** 

Xylene:

Assessment : May cause respiratory irritation.

Deltamethrin (ISO):

Assessment : May cause respiratory irritation.

Solvent naphtha (petroleum), light aromatic:

Assessment : May cause drowsiness or dizziness.

Methanol:

Target Organs : optic nerve, Central nervous system

Assessment : Causes damage to organs.

STOT-repeated exposure

Causes damage to organs (Central nervous system, Immune system) through prolonged or repeated exposure if swallowed.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if

May cause damage to organs (Auditory system) through prolonged or repeated exposure.

**Components:** 

Ethylbenzene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

centrations of >0.2 to 1 mg/l/6h/d.

Xylene:

Routes of exposure : inhalation (vapor)
Target Organs : Auditory system

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.2 to 1 mg/l/6h/d.

Deltamethrin (ISO):

Routes of exposure : Ingestion

Target Organs : Central nervous system, Immune system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

Routes of exposure : inhalation (dust/mist/fume)
Target Organs : Central nervous system

Assessment : Causes damage to organs through prolonged or repeated

exposure.

2,6-Di-tert-butyl-p-cresol:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

**Components:** 

Ethylbenzene:

Species : Rat

LOAEL : 0.868 mg/l
Application Route : inhalation (vapor)

Exposure time : 13 Weeks

Species : Rat
NOAEL : 75 mg/kg
LOAEL : 250 mg/kg
Application Route : Ingestion

Method : OECD Test Guideline 408

Xylene:

Species : Rat

LOAEL : > 0.2 - 1 mg/l
Application Route : inhalation (vapor)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

Species : Rat
LOAEL : 150 mg/kg
Application Route : Ingestion
Exposure time : 90 Days

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Deltamethrin (ISO):

Species : Rat, male and female

NOAEL : 1 mg/kg
LOAEL : 2.5 mg/kg
Application Route : Oral
Exposure time : 13 Weeks
Target Organs : Nervous sy

Target Organs : Nervous system Symptoms : hyperexcitability

Species : Rat LOAEL : 3 mg/m3

Application Route : inhalation (dust/mist/fume)
Exposure time : 2 wk / 5 d/wk / 6 h/d

Symptoms : Local irritation, respiratory tract irritation

Species : Dog
NOAEL : 0.1 mg/kg
LOAEL : 1 mg/kg
Application Route : Oral
Exposure time : 13 Weeks

Target Organs : Nervous system

Symptoms : Dilatation of the pupil, Vomiting, Tremors, Diarrhea, Salivation

Species : Rat

NOAEL : 14 mg/kg

LOAEL : 54 mg/kg

Application Route : Oral

Exposure time : 91 d

Target Organs : Nervous system

Species : Mouse
LOAEL : 6 mg/kg
Application Route : Oral
Exposure time : 12 Weeks
Target Organs : Immune system
Symptoms : immune system effects

2,6-Di-tert-butyl-p-cresol:

Species : Rat
NOAEL : 25 mg/kg
Application Route : Ingestion
Exposure time : 22 Months

Solvent naphtha (petroleum), light aromatic:

Species : Rat
LOAEL : 500 mg/kg
Application Route : Ingestion
Exposure time : 28 Days

**Aspiration toxicity** 

May be fatal if swallowed and enters airways.

according to the OSHA Hazard Communication Standard



## Deltamethrin (with Xylene) Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

#### **Components:**

#### Ethylbenzene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### Xylene:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

### Solvent naphtha (petroleum), light aromatic:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

#### **Experience with human exposure**

### **Components:**

Deltamethrin (ISO):

Inhalation : Symptoms: respiratory tract irritation, Dizziness, Sweating,

Headache, Nausea, Vomiting, anorexia, Fatigue, tingling,

Palpitation, Blurred vision, muscle twitching

Skin contact : Symptoms: Skin irritation, Erythema, pruritis, Headache, Nau-

sea, Vomiting, Dizziness, tingling, Sweating, muscle twitching,

Blurred vision, Fatigue, anorexia, Allergic reactions

Ingestion : Symptoms: muscle pain, Small pupils

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Components:**

#### Ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.8 - 2.4 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 3.6

mg/l

Exposure time: 96 h

NOEC (Pseudokirchneriella subcapitata (green algae)): 3.4

mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (water flea)): 0.96 mg/l

Exposure time: 7 d

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Toxicity to microorganisms : EC50 (Nitrosomonas sp.): 96 mg/l

Exposure time: 24 h

Xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 13.5 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

EC50 (Skeletonema costatum (marine diatom)): 10 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic tox-

icity)

NOEC (Danio rerio (zebra fish)): > 0.1 - < 1 mg/l

Exposure time: 35 d

Method: OECD Test Guideline 210

Remarks: Based on data from similar materials

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

EL10 (Daphnia magna (Water flea)): > 1 - 10 mg/l

Exposure time: 21 d

Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Deltamethrin (ISO):

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): 0.00048

mg/l

Exposure time: 96 h

LC50 (Oncorhynchus mykiss (rainbow trout)): 0.00039 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Mysidopsis bahia (opossum shrimp)): 0.0037 µg/l

Exposure time: 48 h

EC50 (Daphnia magna (Water flea)): 0.0035 mg/l

Exposure time: 48 h

LC50 (Gammarus fasciatus (freshwater shrimp)): 0.0003 µg/l

Exposure time: 96 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 9.1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

according to the OSHA Hazard Communication Standard



## Deltamethrin (with Xylene) Formulation

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 0.000022

mg/l

Exposure time: 36 d

NOEC (Pimephales promelas (fathead minnow)): 0.000017

mg/l

Exposure time: 260 d

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.0041 µg/l

Exposure time: 21 d

2,6-Di-tert-butyl-p-cresol:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 0.57 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0.48 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.24

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0.24

ma/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oryzias latipes (Japanese medaka)): 0.053 mg/l

Exposure time: 30 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): 0.316 mg/l

Exposure time: 21 d

Toxicity to microorganisms

EC50: > 10,000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Solvent naphtha (petroleum), light aromatic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 8.2 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 4.5 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (microalgae)): 3.1 mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (microalgae)): 0.5

mg/l

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR (Daphnia magna (Water flea)): 2.6 mg/l

Exposure time: 21 d

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 211

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Method: DIN 38412

Toxicity to algae/aquatic

plants

ErC50 (Raphidocelis subcapitata (freshwater green alga)):

22,000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l

Exposure time: 3 h

Test substance: Neutralized product Method: OECD Test Guideline 209

### Persistence and degradability

#### **Components:**

Ethylbenzene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 70 - 80 % Exposure time: 28 d

Xylene:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 70 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

### Deltamethrin (ISO):

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Stability in water : Hydrolysis: 0 %(30 d)

2,6-Di-tert-butyl-p-cresol:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 4.5 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Solvent naphtha (petroleum), light aromatic:

Biodegradability : Result: Inherently biodegradable.

Biodegradation: 94 % Exposure time: 25 d

Methanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 95 % Exposure time: 20 d

Bioaccumulative potential

**Components:** 

**Ethylbenzene:** 

Partition coefficient: n-

octanol/water

log Pow: 3.6

Xylene:

Partition coefficient: n-

octanol/water

log Pow: 3.16

Remarks: Calculation

Deltamethrin (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)

Bioconcentration factor (BCF): 1,800

Partition coefficient: n-

octanol/water

log Pow: 4.6

2,6-Di-tert-butyl-p-cresol:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 330 - 1,800

Partition coefficient: n-

octanol/water

log Pow: 5.1

Methanol:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)

Bioconcentration factor (BCF): < 10

Partition coefficient: n-

octanol/water

log Pow: -0.77

according to the OSHA Hazard Communication Standard



# **Deltamethrin (with Xylene) Formulation**

Version **Revision Date:** SDS Number: Date of last issue: 06/26/2024 09/28/2024 2972467-00018 Date of first issue: 07/02/2018 6.3

#### Mobility in soil

#### Components:

Deltamethrin (ISO):

Distribution among environ-

mental compartments

Other adverse effects

No data available

log Koc: 7.2

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging Empty containers should be taken to an approved waste

handling site for recycling or disposal.

Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other

sources of ignition. They may explode and cause injury and/or

If not otherwise specified: Dispose of as unused product.

### **SECTION 14. TRANSPORT INFORMATION**

## International Regulations

**UNRTDG** 

**UN** number UN 1992

Proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.

(Ethylbenzene, Xylene)

Class 3 Subsidiary risk 6.1 Packing group Ш Labels 3(6.1)Environmentally hazardous no

IATA-DGR

UN/ID No. UN 1992

Flammable liquid, toxic, n.o.s. Proper shipping name

(Ethylbenzene, Xylene)

Class 3 Subsidiary risk 6.1 Packing group Ш

Labels Flammable Liquids, Toxic

Packing instruction (cargo

aircraft)

Packing instruction (passen-

355

ger aircraft)

**IMDG-Code** 

UN 1992 UN number

Proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.

366

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

(Ethylbenzene, Xylene, Deltamethrin (ISO))

Class : 3
Subsidiary risk : 6.1
Packing group : III
Labels : 3 (6.1)
EmS Code : F-E, S-D
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 1992

Proper shipping name : Flammable liquids, toxic, n.o.s.

(Ethylbenzene, Xylene)

Class : 3
Subsidiary risk : 6.1
Packing group : III

Labels : FLAMMABLE LIQUID, TOXIC

ERG Code : 131

Marine pollutant : yes(Deltamethrin (ISO))

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RC	
		(lbs)	(lbs)	
Xylene	1330-20-7	100	271	
Ethylbenzene	100-41-4	1000	2583	

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity
Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

Skin corrosion or irritation

Serious eye damage or eye irritation

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Ethylbenzene 100-41-4 >= 30 - < 50 %

Xylene 1330-20-7 >= 30 - < 50 %

4-Nonylphenol, 127087-87-0 >= 10 - < 20 %

branched, ethox-

ylated

### **US State Regulations**

### Pennsylvania Right To Know

 Ethylbenzene
 100-41-4

 Xylene
 1330-20-7

 4-Nonylphenol, branched, ethoxylated
 127087-87-0

 Deltamethrin (ISO)
 52918-63-5

 2,6-Di-tert-butyl-p-cresol
 128-37-0

 Methanol
 67-56-1

 Acetic acid
 64-19-7

### California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and

Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### California List of Hazardous Substances

 Ethylbenzene
 100-41-4

 Xylene
 1330-20-7

 2,6-Di-tert-butyl-p-cresol
 128-37-0

### **California Permissible Exposure Limits for Chemical Contaminants**

 Ethylbenzene
 100-41-4

 Xylene
 1330-20-7

 2,6-Di-tert-butyl-p-cresol
 128-37-0

### The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

### **SECTION 16. OTHER INFORMATION**

### **Further information**


according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse)

according to the OSHA Hazard Communication Standard



## **Deltamethrin (with Xylene) Formulation**

Version Revision Date: SDS Number: Date of last issue: 06/26/2024 6.3 09/28/2024 2972467-00018 Date of first issue: 07/02/2018

Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

**Data Sheet** 

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 09/28/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8