

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version 3.1 Revision Date: 09/30/2023 SDS Number: 10821631-00004 Date of last issue: 04/04/2023
Date of first issue: 07/28/2022

SECTION 1. IDENTIFICATION

Product name : Flugestone Acetate Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Reproductive toxicity : Category 1B
Specific target organ toxicity : Category 2 (Adrenal gland)
- repeated exposure (Oral)

GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
H360FD May damage fertility. May damage the unborn child.
H373 May cause damage to organs (Adrenal gland) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version 3.1 Revision Date: 09/30/2023 SDS Number: 10821631-00004 Date of last issue: 04/04/2023
Date of first issue: 07/28/2022

P308 + P313 IF exposed or concerned: Get medical attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Dust contact with the eyes can lead to mechanical irritation.
Contact with dust can cause mechanical irritation or drying of the skin.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
flugestone 17-acetate	2529-45-5	4
Polyethylene glycol	25322-68-3	4

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : If in eyes, rinse well with water.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May damage fertility. May damage the unborn child.
May cause damage to organs through prolonged or repeated exposure if swallowed.
Contact with dust can cause mechanical irritation or drying of the skin.
- Protection of first-aiders : Dust contact with the eyes can lead to mechanical irritation.
First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal.
Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).
Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

-
- | | | |
|-----------------------------|---|---|
| Technical measures | : | Static electricity may accumulate and ignite suspended dust causing an explosion.
Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Do not breathe dust.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep container tightly closed.
Minimize dust generation and accumulation.
Keep container closed when not in use.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment. |
| Conditions for safe storage | : | Keep in properly labeled containers.
Store locked up.
Keep tightly closed.
Store in accordance with the particular national regulations. |
| Materials to avoid | : | Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases |

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

- | | |
|--------------------------------------|--|
| inert or nuisance dust | 50 Million particles per cubic foot
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3 |
| | 15 mg/m ³
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3 |
| | 5 mg/m ³
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3 |
| | 15 Million particles per cubic foot
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3 |
| Dust, nuisance dust and particulates | 10 mg/m ³
Value type (Form of exposure): PEL (Total dust) |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version 3.1 Revision Date: 09/30/2023 SDS Number: 10821631-00004 Date of last issue: 04/04/2023
Date of first issue: 07/28/2022

Basis: CAL PEL

5 mg/m³

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
flugestone 17-acetate	2529-45-5	TWA	0.2 µg/m ³ (OEB 5)	Internal
		Wipe limit	2 µg /100 cm ²	Internal
Polyethylene glycol	25322-68-3	TWA (aerosol)	10 mg/m ³	US WEEL

Engineering measures : Use closed processing systems or containment technologies to control at source (e.g., glove boxes/isolators) and to prevent leakage of compounds into the workplace. All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment. No open handling permitted. Totally enclosed processes and materials transport systems are required. Operations require the use of appropriate containment technology designed to prevent leakage of compounds into the workplace.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

Eye protection : Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

Hygiene measures : Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially contaminated clothing.

: If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.

When using do not eat, drink or smoke.

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	powder
Color	:	white
Odor	:	odorless
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	May form explosive dust-air mixture during processing, handling or other means.
Flammability (liquids)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	Not applicable
Relative vapor density	:	Not applicable
Relative density	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

Density	:	No data available
Solubility(ies)	:	
Water solubility	:	partly miscible
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Molecular weight	:	No data available
Particle size	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	May form explosive dust-air mixture during processing, handling or other means. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks. Avoid dust formation.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:

flugestone 17-acetate:

Acute oral toxicity	:	Remarks: No data available
---------------------	---	----------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

Polyethylene glycol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Components:

flugestone 17-acetate:

Remarks : No data available

Polyethylene glycol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Not classified based on available information.

Components:

flugestone 17-acetate:

Remarks : No data available
Mild eye irritation

Polyethylene glycol:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

flugestone 17-acetate:

Remarks : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

Polyethylene glycol:

Test Type	: Maximization Test
Routes of exposure	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

flugestone 17-acetate:

Genotoxicity in vitro	: Test Type: Microbial mutagenesis assay (Ames test) Result: negative
-----------------------	--

Test Type: Mouse Lymphoma Result: negative

Test Type: Chromosomal aberration Test system: Human lymphocytes Result: negative

Genotoxicity in vivo	: Remarks: No data available
----------------------	------------------------------

Germ cell mutagenicity - Assessment	: Weight of evidence does not support classification as a germ cell mutagen.
-------------------------------------	--

Polyethylene glycol:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on data from similar materials
-----------------------	---

Carcinogenicity

Not classified based on available information.

Components:

flugestone 17-acetate:

Remarks	: No data available
---------	---------------------

Carcinogenicity - Assessment	: No data available
------------------------------	---------------------

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version 3.1 Revision Date: 09/30/2023 SDS Number: 10821631-00004 Date of last issue: 04/04/2023
Date of first issue: 07/28/2022

Reproductive toxicity

May damage fertility. May damage the unborn child.

Components:

flugestone 17-acetate:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rabbit
Application Route: Oral
General Toxicity Parent: NOAEL: 0.003 mg/kg body weight
Fertility: NOAEL: 0.003 mg/kg body weight

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 0.1 mg/kg body weight
Teratogenicity: NOAEL: 10 mg/kg body weight
Embryo-fetal toxicity.: NOAEL: 10 mg/kg body weight

Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Oral
General Toxicity Maternal: NOAEL: 0.01 mg/kg body weight
Embryo-fetal toxicity.: NOAEL: 0.04 mg/kg body weight

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, based on animal experiments., Clear evidence of adverse effects on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Adrenal gland) through prolonged or repeated exposure if swallowed.

Components:

flugestone 17-acetate:

Routes of exposure : Oral
Target Organs : Adrenal gland
Assessment : Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity

Components:

flugestone 17-acetate:

Species : Rat
NOAEL : 0.2 mg/kg
Application Route : Oral
Exposure time : 90 d

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

Number of exposures : daily
Target Organs : Adrenal gland

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

flugestone 17-acetate:

General Information : May cause adverse reproductive effects.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

flugestone 17-acetate:

Toxicity to fish (Chronic toxicity) : NOEC (Zebrafish): < 0.0004 µg/l
Exposure time: 32 d
Method: OECD Test Guideline 210
Remarks: Based on data from similar materials

Polyethylene glycol:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Polyethylene glycol:

Biodegradability : Result: rapidly degradable
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Polyethylene glycol:

Partition coefficient: n-octanol/water : log Pow: < 3

Mobility in soil

No data available

Other adverse effects

No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version 3.1 Revision Date: 09/30/2023 SDS Number: 10821631-00004 Date of last issue: 04/04/2023
Date of first issue: 07/28/2022

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(flugestone 17-acetate)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.
(flugestone 17-acetate)

Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 956
Packing instruction (passenger aircraft) : 956
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3077
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,
N.O.S.
(flugestone 17-acetate)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 3077
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

(flugestone 17-acetate)

Class	: 9
Packing group	: III
Labels	: CLASS 9
ERG Code	: 171
Marine pollutant	: yes(flugestone 17-acetate)
Remarks	: Above applies only to containers over 119 gallons or 450 liters. Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	: Combustible dust Reproductive toxicity Specific target organ toxicity (single or repeated exposure)
-----------------------------	---

SARA 313	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
-----------------	---

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Polyethylene glycol	25322-68-3
Hydroxypropyl cellulose	9004-64-2
flugestone 17-acetate	2529-45-5

The ingredients of this product are reported in the following inventories:

AICS	: not determined
DSL	: not determined
IECSC	: not determined

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard




Flugestone Acetate Formulation

Version 3.1 Revision Date: 09/30/2023 SDS Number: 10821631-00004 Date of last issue: 04/04/2023
Date of first issue: 07/28/2022

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

CAL PEL	:	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
CAL PEL / PEL	:	Permissible exposure limit
OSHA Z-3 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Flugestone Acetate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 04/04/2023
3.1	09/30/2023	10821631-00004	Date of first issue: 07/28/2022

Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/30/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8