according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

SECTION 1. IDENTIFICATION

Product name : Ovipast Plus Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc Address : 126 E. Lincoln Avenue

Rahway, New Jersey U.S.A. 07065

Telephone : 908-740-4000 Emergency telephone : 1-908-423-6000

E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary medicine Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization : Category 1

GHS label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : Prevention:

P261 Avoid breathing mist or vapors.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P333 + P313 If skin irritation or rash occurs: Get medical atten-

tion.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

Other hazards

None known.

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 04/06/2024 6344704-00008 Date of first issue: 09/16/2020 3.0

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Aluminum hydroxide	21645-51-2	25
Antigen	Not Assigned	> 1.5 - < 2.5
Maleic acid	110-16-7	0.23

SECTION 4. FIRST AID MEASURES

General advice In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact In case of contact, immediately flush skin with soap and plenty

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Flush eyes with water as a precaution. In case of eye contact

Get medical attention if irritation develops and persists.

: If swallowed, DO NOT induce vomiting. If swallowed

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delaved

May cause an allergic skin reaction.

Protection of first-aiders First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Treat symptomatically and supportively. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fiahtina

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod- :

Carbon oxides Metal oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 04/06/2024 6344704-00008 Date of first issue: 09/16/2020 3.0

Remove undamaged containers from fire area if it is safe to do

Evacuate area.

Special protective equipment :

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).

Environmental precautions Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g., by containment or

oil barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Soak up with inert absorbent material.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation Advice on safe handling Use only with adequate ventilation. Do not get on skin or clothing.

Avoid breathing mist or vapors.

Do not swallow.

Avoid contact with eyes.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure

assessment

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Do not store with the following product types: Materials to avoid

Strong oxidizing agents

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum hydroxide	21645-51-2	TWA (Respirable particulate matter)	1 mg/m³ (Aluminum)	ACGIH

Engineering measures: Use appropriate engineering controls and manufacturing

technologies to control airborne concentrations (e.g., drip-

less quick connections).

All engineering controls should be implemented by facility design and operated in accordance with GMP principles to

Laboratory operations do not require special containment.

protect products, workers, and the environment.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and

use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Chemical-resistant gloves

Eye protection : Wear safety glasses with side shields or goggles.

If the work environment or activity involves dusty conditions,

mists or aerosols, wear the appropriate goggles.

Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or

aerosols.

Skin and body protection

Hygiene measures

: Work uniform or laboratory coat.

If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the

working place.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash contaminated clothing before re-use.

The effective operation of a facility should include review of

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version 3.0

Revision Date: 04/06/2024

SDS Number: 6344704-00008

Date of last issue: 09/30/2023 Date of first issue: 09/16/2020

engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : suspension

Color : off-white to beige, opaque

Odor : No data available

Odor Threshold : No data available

pH : 6.1 - 6.9

Melting point/freezing point : No data available

Initial boiling point and boiling

range

No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapor pressure : similar to water

Relative vapor density : No data available

Relative density : 1

Density : 1 g/cm³

similar to water

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : Not applicable

Particle characteristics

Particle size : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reac- : Can react with strong oxidizing agents.

tions

Conditions to avoid : None known. Incompatible materials : Oxidizing agents

Hazardous decomposition : No hazardous decomposition products are known.

products

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Components:

Aluminum hydroxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 423

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 5.09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Maleic acid:

Acute oral toxicity : LD50 (Rat): > 300 - 2,000 mg/kg

Method: OECD Test Guideline 401

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): 1,560 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Aluminum hydroxide:

Species : Rabbit

Method : OECD Test Guideline 404

Result : No skin irritation

Maleic acid:

Species : in vitro membrane barrier
Method : OECD Test Guideline 435

Result : Corrosive after 3 minutes to 1 hour of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Aluminum hydroxide:

Species : Rabbit

Result : No eye irritation

Method : OECD Test Guideline 405

Maleic acid:

Result : Irreversible effects on the eye Remarks : Based on skin corrosivity.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Aluminum hydroxide:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig

Method : OECD Test Guideline 406

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Result : negative

Maleic acid:

Test Type : Maximization Test Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : positive

Assessment : Probability or evidence of skin sensitization in humans

Germ cell mutagenicity

Not classified based on available information.

Components:

Aluminum hydroxide:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Result: positive

Remarks: Based on data from similar materials

Test Type: DNA damage and repair, unscheduled DNA syn-

thesis in mammalian cells (in vitro)

Result: equivocal

Remarks: Based on data from similar materials

Test Type: in vitro micronucleus test

Result: positive

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Maleic acid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Carcinogenicity

Not classified based on available information.

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Components:

Aluminum hydroxide:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 86 weeks Result : negative

Remarks : Based on data from similar materials

Maleic acid:

Species : Rat
Application Route : Ingestion
Exposure time : 2 Years
Result : negative

Remarks : Based on data from similar materials

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Aluminum hydroxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

Maleic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 04/06/2024 6344704-00008 Date of first issue: 09/16/2020 3.0

Species: Rat

Application Route: Ingestion

Result: negative

Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

Components:

Maleic acid:

Assessment May cause respiratory irritation.

Remarks Based on national or regional regulation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Aluminum hydroxide:

Species Rat

NOAEL : > 100 mg/kgApplication Route : Ingestion Exposure time 364 Davs

OECD Test Guideline 426 Method

Remarks Based on data from similar materials

Rat Species

NOAEL > 0.2 mg/kg

Application Route inhalation (dust/mist/fume)

Exposure time 12 Months

Remarks Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

plants

Components:

Aluminum hydroxide:

Toxicity to fish : LL50 (Salmo trutta (brown trout)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic EL50 (Selenastrum capricornutum (green algae)): > 100 mg/l

Exposure time: 96 h

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Maleic acid:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): > 10 - 100

mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 42.81 mg/l

Exposure time: 48 h

Test substance: Neutralized product Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Pseudokirchneriella subcapitata (green algae)): 74.35

mg/l

Exposure time: 72 h

Test substance: Neutralized product Method: OECD Test Guideline 201

EC10 (Pseudokirchneriella subcapitata (green algae)): 11.8

mg/l

Exposure time: 72 h

Test substance: Neutralized product Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC (Daphnia magna (Water flea)): > 1 mg/l

Exposure time: 21 d

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): 44.6 mg/l

Exposure time: 18 h

Test substance: Neutralized product

Method: DIN 38 412 Part 8

Persistence and degradability

Components:

Maleic acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 97 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

Maleic acid:

Partition coefficient: n-

: log Pow: -1.3

octanol/water

Mobility in soil
No data available

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Formaldehyde	50-00-0	100	200000

SARA 304 Extremely Hazardous Substances Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
Formaldehyde	50-00-0	100	200000	

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

Thiomersal 54-64-8 0.013 %

US State Regulations

Pennsylvania Right To Know

 Water
 7732-18-5

 Aluminum hydroxide
 21645-51-2

 Maleic acid
 110-16-7

 Formaldehyde
 50-00-0

 Thiomersal
 54-64-8

California Prop. 65

WARNING: This product can expose you to chemicals including Formaldehyde, which is/are known to the State of California to cause cancer, and

Thiomersal, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

AICS : not determined

DSL : not determined

IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information


according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: HMIS - Hazardous Materials Identification System: IARC -International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance

according to the OSHA Hazard Communication Standard



Ovipast Plus Formulation

Version Revision Date: SDS Number: Date of last issue: 09/30/2023 3.0 04/06/2024 6344704-00008 Date of first issue: 09/16/2020

Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 04/06/2024

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8